

International Standard Specifications Accepted

Arkan Group supplies Penetration Bitumen Grades in correspondence to ASTM D946-09 including:

Bitumen Penetration Grade 60-70

- **Density:** 06/1-01/1.
- **Penetration Rate at 25C:** 60-70.
- **Softening Point °C:** 49-56.
- **Ductility 25C (cm):** Min 100.
- **Flash Point °C:** Min250.
- **Solubility Disulphide % weight:** 5/99.
- **Stain Test:** Negative.
- **Weight Loss by Heating %weight:** Max 2/0.
- **Weight Loss by Heating %:** Max 20.

-Depending on the origin, these specifications may vary slightly. However, these variations will always be within the standards accepted in the international market.

- All Specifications will be confirmed at the time of establishing the contract with our Supplier. If for any reason there are any variations in the Specifications, they shall be confirmed with our Buyer through an Addendum to the Draft between the parties (Seller and Buyer).

- All prices and quantities, for each transaction, will be confirmed with our suppliers. Therefore, the Buyer must wait for such confirmation (SCO-FCO) to proceed with the transaction.

☎ +97142100300

@ info@arkan-group.com

🌐 www.arkan-group.com

📍 Office 205, Aspect Tower, Zone B Business Bay, Dubai