

International Standard Specifications Accepted

Granular Sulphur Specifications:

• **Purity(dry,wt%):** 99.50 min.

• Ash Content(wt%): 0.05 max.

Moisture(wt%): 0.50 max.

• **Organic(wt%):** 0.05 max.

• Acidity(wt%): 0.02 max.

• Colour: Bright Yellow.

• Form: Granular.

Lump Sulphur Specifications (99.5%-99.99%):

• **Purity:** 99.50 min.

• **Ash:** 0.4 max.

• Sulphuric Acid: 0.02 max.

• Organic: 0.5 max.

Moisture: 1.0 max.

• **Colour:** Bright-Dark Yellow.

• Form: Lump.

• Mechanical Impurities: None.

• Max Particle Size:150mm.

(+97142100300

- @ info@arkan-group.com
- # www.arkan-group.com
- Office 205, Aspect Tower, Zone B Business Bay, Dubai



- Average Particle Suze: 50mm.
- Packing: 50kgs bag- Jumbo Bag- Bulk.
- Certified By: SGS.

Powder Sulphur Specifications:

- **Purity:** 99.50 min.
- Dry Sieve Test 200 B.S.S: 80% min.
- Dry Sieve Test 350 B.S.S: 60% max.
- Dry Sieve Test 100 B.S.S: 95% max.
- Acidity(As H2S04): 1.0% max.
- Colour: Bright Yellow.
- Form: Powder.
- Ash Content: 1.0%Max.
- Melting Point: 116-119 Degree Centigrade.
- Depending on the origin, these specifications may vary slightly. However, these variations will always be within the standards accepted in the international market.
- All Specifications will be confirmed at the time of establishing the contract with our Supplier. If for any reason there are any variations in the Specifications, they shall be confirmed with our Buyer through an Addendum to the Draft between the parties (Seller and Buyer).
- All prices and quantities, for each transaction, will be confirmed with our suppliers. Therefore, the Buyer must wait for such confirmation (SCO-FCO) to proceed with the transaction.

(0 +97142100300

- @ info@arkan-group.com
- # www.arkan-group.com
- Office 205, Aspect Tower, Zone B Business Bay, Dubai