

International Standard Specifications Accepted

● Fuel Oil 380 CST Specifications:

- Density(kg/m³): 990 max.
- K. Viscosity(CST): 380 max.
- Pour Point(DC): 32 max.
- Flash Point(DC): 65 min.
- Sulphur Total(wt %): 3.5 max.
- Carbon Residue(wt %): 15 max.
- Ash(wt %): 0.15 max.
- Water and Sediment(vol %): 1.0 max.
- Calorific Value(mj/kg): 41.7 min.

Fuel Oil 180 CST Specifications:

- Density(kg/m³): 991 max.
- K. Viscosity(CST): 180-380 max.
- Pour Point(DC): 10-30 max.
- Flash Point(DC): 60 min.
- Carbon Residue(% m): 18-20.
- Water(%): 1.
- Sulphur Total(wt %): 3-3.5 max.
- Vanadium(mg/kg): 300-500.
- Aluminium and Silicon(mg/kg): 80 max.
- Acid Number (mg KOH/g): 3 max.
- Total Sediment(% m): 0.1.
- CCAI: 860.
- Ash(wt %): 0.15 max.

☎ +97142100300

@ info@arkan-group.com

🌐 www.arkan-group.com

📍 Office 205, Aspect Tower, Zone B Business Bay, Dubai

Fuel Oil 280 CST Specifications:

- **Density(kg/m³):** 970 max.
- **K. Viscosity(CST):** 280 max.
- **Pour Point(DC):** 24 max.
- **Flash Point(DC):** 65 min.
- **Sulphur Total(wt %):** 3.5 max.
- **Carbon Residue(wt %):** 15 max.
- **Ash(wt %):** 0.05 max.
- **Water and Sediment(vol %):** 0.5 max.
- **Calorific Value(mj/kg):** 41.8 min.
- **Visco Rodwood(SPECS):** 2500 max.

-Depending on the origin, these specifications may vary slightly. However, these variations will always be within the standards accepted in the international market.

-All Specifications will be confirmed at the time of establishing the contract with our Supplier. If for any reason there are any variations in the Specifications, they shall be confirmed with our Buyer through an Addendum to the Draft between the parties (Seller and Buyer).

-All prices and quantities, for transactions, will be confirmed with our suppliers. Therefore, the Buyer must wait for such confirmation (SCO-FCO) to proceed with the transaction.

☎ +97142100300

@ info@arkan-group.com

🌐 www.arkan-group.com

📍 Office 205, Aspect Tower, Zone B Business Bay, Dubai